

Application No. 10/072,663
Amendment dated January 19, 2006
Reply to Office Action of October 19, 2005

Docket No.: 08212/000S007-US0/NC31530US

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A system for a secure key distribution protocol in AAA for Mobile IP, comprising:

[[a]] an MN that is configured to: generate a Reg-Req message that includes Diffie-Hellman parameters that are used to generate session keys and produce signatures; initiate an authentication session by sending the Reg-Req message; receive a Reg-Reply message that includes session keys that may be used to directly communicate with the AAAH, AAAP, HA, and FA nodes while the MN is in a foreign authority, wherein the session keys are encrypted and wherein the session keys include a first at least one key, a second at least one key, and a third at least one key;

[[a]] an FA that is configured to: receive the Reg-Req message; ensure that the authentication session is valid; and when valid, sign and send the Reg-Req message; otherwise, end the authentication session; receive, and authenticate, decrypt the Reg-Reply message; decrypt at least one key of the session keys; sign, and send the Reg-Reply message to the MN;

an AAAP that is configured to: receive and authenticate the Reg-Req message; generate a first at least one key of the session keys using the Diffie-Hellman Diffie-Hellman algorithm and the Diffie-Hellman parameters; add an identifier relating to the Reg-Req message; sign and send the Reg-Req message; receive, authenticate, sign and send the Reg-Reply message to the FA;

an AAAH that is configured to: receive and authenticate the Reg-Req message; generate a second at least one key of the session keys; sign and send the Reg-Req message; receive and authenticate the Reg-Reply message; generate a third at least one key of the session keys; encrypt the session keys; sign and send the Reg-Reply message to the AAAP;

[[a]] an HA that is configured to: receive the Reg-Req message; prepare a Reg-Reply message in response to the Reg-Req message; and send the Reg-Reply message to the AAAH.

2. (Original) The system of Claim 1, wherein the Diffie-Hellman parameters include an n , a g , and a p parameter; wherein the parameters are used to generate the session keys and are used in signing the Reg-Req message and the Reg-Reply message.

{S:\08212\000S007-US0\80049421.DOC (01/19/2006 16:02 FAX 2062628901) } 3

Application No. 10/072,663
Amendment dated January 19, 2006
Reply to Office Action of October 19, 2005

Docket No.: 08212/000S007-US0/NC31530US

3. (Currently Amended) The system of Claim 2, wherein the Reg-Req message and the Reg-Reply message include[[s]] an identifier relating to where the message originated, wherein the identifier is selected from an NAI and a new random nonce.

4. (Original) The system of Claim 3, wherein the Reg-Req message and the Reg-Reply message are signed using a security association between a sender of the Reg-Req message and the Reg-Reply message and a receiver of the Reg-Req message and the Reg-Reply message.

5. (Currently Amended) The system of Claim 4, wherein the AAAF is further configured to: choose a secret random number y to calculate a parameter $q = g^y \text{ mod } n$ according to the ~~Diffie-Hellman~~ Diffie-Hellman algorithm that is used in generating the session keys.

6. (Original) The system of Claim 4, wherein authenticating the Reg-Req message and the Reg-Reply message further comprises ensuring that the Reg-Req message and the Reg-Reply message came from the sender by checking the signature relating to a security association between the sender and the receiver.

7. (Original) The system of Claim 6, wherein the AAAF is further configured to determine the AAAH for the MN in response to the identifier associated with the MN.

8. (Currently Amended) The system of Claim 7, wherein the AAAF is further configured to store a time associated with the initiation of the authentication session in order to prevent a Reply message ~~fail~~ failure.

9. (Original) The system of Claim 8, wherein the AAAH is further configured to protect the authentication process from a replay attack, and when the AAAH does not recognize the MN, generate an error.

{S:\08212\000S007-US0\80049421.DOC (00000000000000000000000000000000) } 4

Docket No.: 08212/000S007-US0/NC31530US

establishing a secure association between the AAAF and the MN.

16. (Original) The method of Claim 15, further comprising determining when a signature is an authentic signature based on the secure associations and the session keys.

17. (Original) The method of Claim 16, wherein establishing the secure associations between the MN, the AAAH, the AAAP, the HA, and the FA to help ensure secure communication, further comprises:

signing the Reg-Req message and the Reg-Reply message using the session keys; and authenticating the received Reg-Req message and the Reg-Reply message.

18. (Original) The method of Claim 17, wherein creating the session keys further comprises utilizing Diffie-Hellman parameters and the Diffie-Hellman algorithm.

19. (Original) The method of Claim 18, wherein the Reg-Req message includes an NAI associated with the MN, a timestamp, a challenge issued by the FA, and the Diffie-Hellman parameters.

20. (Original) The method of Claim 19, wherein the Reg-Reply message includes an identifier and the session keys.

{S:\08212\000S007-US0\80049421.DOC [REDACTED] }6